

Pendant Installation

CAUTION

Be sure the electricity to the system you are working on is turned off; either the fuse removed or the circuit breaker set to off. **IF YOU ARE UNCLEAR ON HOW TO PROCEED, CONTACT A QUALIFIED ELECTRICIAN.**

THIS FIXTURE IS INTENDED FOR INSTALLATION IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE AND REGULATIONS. TO ASSURE FULL COMPLIANCE WITH LOCAL CODES AND REGULATIONS, CONSULT WITH YOUR LOCAL ELECTRICAL INSPECTOR BEFORE INSTALLATION.

PRE-INSTALLATION

Install 4"x4" electric box capable of holding 15 pounds with appropriate power.

CANOPY INSTALLATION

Attach crossbar, canopy, electrical wires, canopy cover, and canopy nut.

TO ADJUST WIRE LENGTH

Hanging wire is sent fully extended. To adjust wire length, push inset of hanging nipple (on canopy) and push or pull cord into or out of canopy. Release inset on nipple to secure. Three or more feet of wire can be pushed into canopy which will eventually fill up. To shorten wire further, wire must be cut and reconnected using the existing wire nuts.

TO INSTALL GLOBES

Press together tabs on either side of can, insert into glass globe, release tabs. Do not release globe until both tabs click and are fully extended and globe is securely attached.